

# R & H Chrome Alloy WELD-ON OPENERS & PLOW PARTS

Learn more - [www.rhmachine.com](http://www.rhmachine.com) 1-800-321-6568

## R & H CHROME ALLOY WELD-ON OPENERS

R & H Machine offers a wide variety of weld-on openers, many of which are pre-welded onto either 3/8" or 3/16" mild-steel backing for ease of installation. The cap is wider than the backing to reduce wear on the shank.

### RH 442 B WELD-ON SMALL SPIKE POINT WITH BACKING

Length: 4"  
Width: 2"  
Notch:

Length: 1-3/8"  
Width: 3/4"

Thickness: 7/8" (including 3/8" steel backing)



### RH 443 B WELD-ON LARGE SPIKE POINT WITH BACKING



Length: 5"  
Width: 2-1/2"  
Notch:

Length: 2"  
Width: 3/4"

Thickness: 7/8" (including 3/8" steel backing)

### RH 444 B WELD-ON OPENER WITH BACKING

Length: 4-3/8"  
Width: 3-1/4"  
Notch:

Length: 1/1/2"  
Width: 3/4"

Thickness: 3/8" (including 3/16" steel backing)



### RH 445 B WELD-ON OPENER WITH BACKING



Length: 4-3/8"  
Width: 5-1/8"  
Notch:

Length: 1-7/8"  
Width: 1/2"

Thickness: 7/16" (including 3/16" steel backing)

### RH 440 WELD-ON OPENER

Length: 5"  
Height: 1"  
Thickness: 3/8"



### RH 441 1" WELD-ON OPENER

Sides: 3" x 3-5/8" x 4-3/4"  
Thickness: 1"



### RH 441-.75 3/4" WELD-ON OPENER

Sides: 3" x 3" x 4-1/4"  
Thickness: 3/4"



### RH 441 NR 5/8" ROUNDED WELD-ON OPENER

Sides: 3" x 3-1/2" x 4-5/8"  
Thickness:  
Body: 1/2"  
Nose: 5/8"



### RH 441 NRL 5/8" ROUNDED WELD-ON OPENER

Sides: 3-1/2" x 4-3/4" x 6-7/8"  
Thickness:  
Body: 1/2"  
Nose: 5/8"



### RH 448 WELD-ON POINTED OPENER

Length: 3-1/4"  
Height: 4"  
Thickness: 3/4"



### RH 447 RENOVATOR POINT

To fit: Hay King renovator

Length: 8"  
Height: 6-1/2"



### RH 449 WELD-ON OPENER

Length: 5-1/4"  
Height: 3-3/8"  
Thickness: 3/4"



# R & H Chrome Alloy WELD-ON OPENERS & PLOW PARTS

## R & H CHROME ALLOY OPENERS

### OPENER INSERT / PLANTER

**RH 346**

**RH 346 L**


**RH 346 J**



Length: 3-1/4"  
Height: 5-1/4"  
Thickness: 2"

Length: 3-3/8"  
Height: 7-3/8"  
Thickness: 2"

Length: 3-1/4"  
Height: 7-3/8"  
Thickness: 1-5/8"



**RH 255**

**POINT or OPENER**

**RH 255 S**



Width: 5-1/4"

Height: 7-1/4"  
Thickness: 5/8"



Width: 3-1/2"

## R & H CHROME ALLOY LAND SLIDES

**RH 420 LAND SLIDE**

To fit: JD plow (replaces JD part #57046)

Length: 6-1/2"  
Width: 4"  
Thickness: 1/2"  
Bolt holes: 7/16"



**RH 421 LEFT or RIGHT LAND SLIDE**

To fit: John Deere 845 and Watts plow

Length: 7"  
Width: 4"  
Thickness: 1/2"  
Bolt holes: 7/16"



LEFT



RIGHT

**RH 422 LAND SLIDE**

To fit: JD switch plow  
(replaces JD part #IP60071)

Length: 8-1/8"  
Width: 8-1/8"  
Thickness: 5/8"  
Bolt holes: 7/16"



**RH 425 LEFT or RIGHT LAND SLIDE**

To fit: CaselH plow (replaces Case part #1980947C2)

Length: 6"  
Width: 4-1/2"  
Thickness: 1/2"  
Bolt holes: 7/16"



LEFT



RIGHT

## R & H CHROME ALLOY PLOW PARTS

### R & H CHROME ALLOY MOLDBOARDS

**RH 416 MOLDBOARD COVER**

To fit: Long switch plow



Length: 9-7/8"  
Width: 11-3/4"  
Thickness: 1/2"  
Bolt holes: 1/2"

**RH 417 MOLDBOARD COVER**

To fit: Long switch plow



Length: 9-7/8"  
Width: 11-3/4"  
Thickness: 1/2"  
Bolt holes: 1/2"

NOTE: use 2-RH 416's and 2-RH 417's to make complete moldboard cover.

### R & H CHROME ALLOY WELD-ON PLOW POINTS

**RH 415 LEFT or RIGHT EXTENDED PLOW POINT**

To fit: Wilcox



LEFT

Length: 8-1/2"  
Width: 3"  
Thickness: 7/8"



RIGHT

**RH 418 PLOW POINT**

Length: 10-1/8"  
Height: 5"  
Thickness: 5/8"



**RH 419 LEFT or RIGHT PLOW CAP**



Length: 6"  
Height: 5-1/2"  
Thickness: 1/2"