



# *Setting the Standard for Wear!*

## **R & H Chrome Alloy ROD WEEDER PARTS**

Learn more - [www.rhmachine.com](http://www.rhmachine.com) 1-800-321-6568

R & H Machine offers an extensive line of Chrome Alloy rod weeder wear parts to fit Calkins, Case IH, John Deere, Morris, Flex King, Edwards, Anderson, and Leon. We sell sprockets, wear collars, spools, wear blocks, and boot points. By popular demand, we have added goose-neck points with Chrome Alloy rod installed; and we have Chrome Alloy rod available for you to weld onto the front edge of your goose-neck points. All of our parts are cast of High Chrome Alloy to give many years of reliable service.

R & H Chrome Alloy wear parts have proven themselves in all areas of the country and in all soil types. Our rod weeder wear parts not only last longer than standard parts, but also lengthen the life of the chain and other components in several ways. R & H Chrome Alloy wear parts don't allow the teeth to "hook" as readily, resulting in less stress on the chain and extended chain life. Most of our boot points are made wider than standard parts to give better side plate protection. Our boot points also are made with deeper penetration on the bottom to give better sprocket protection, resulting in prolonged chain and sprocket life.

### **SPROCKETS**

We offer chain drive, rod drive, and idler sprockets.

### **COLLARS**

Collars are used on both sides of drive sprockets, and can be turned to obtain even longer life.

### **GOOSE-NECK POINTS**

We have goose-neck points, with Chrome Alloy rod installed, to fit your rod weeders.

### **SPOOLS**

We have regular spools, barrel spools, and spools with set-screw collars

### **WEAR BLOCKS**

Wear blocks are available to fit all types of our spools.

### **BOOT POINTS**

We have regular, rock, and universal boot points.

### **WELD-ON RODS**

We have Chrome Alloy rod for use on your goose-neck points (see RH 16).



**Weed out the rest---Use the best!!!**

# R & H Chrome Alloy ROD WEEDER PARTS

## TO FIT: INTERNATIONAL

### CENTER DRIVE SPROCKET and COLLAR

- RH 801 CENTER DRIVE SPROCKET**  
**RH 860 WEAR COLLAR** for RH 801



Diameter: 4-7/8"  
 Width: 2"  
 Teeth: 11



Collar diameter:  
 Outside: 3-1/8"  
 Inside: 1-7/8"

NOTE: Please specify 7/8", 1", or hex rod

### SPOOLS and WEAR BLOCK

- RH 862 SPOOL** with SET-SCREW COLLAR

Length: 2-7/8"  
 Diameter: 2-1/2"

NOTE: Please specify 7/8" or 1" rod



- RH 864 SPOOL**

Length: 2-1/8"  
 Diameter: 2-1/2"

NOTE: Please specify 7/8" or 1" rod



- RH 865 WEAR BLOCK** for BOTH

Width: 3-1/8"  
 Holes: 3/8"  
 Hole spacing: 2-1/8"



### GOOSE-NECK POINT

- RH 869 A GOOSE-NECK POINT**

Length: 15"  
 Width: 3-1/2"



Chrome Alloy rod (RH 16) pre-welded onto leading edge of 3/8" T-1 steel.

### IDLER SPROCKET ASSEMBLY

- RH 825 A IDLER SPROCKET** with BUSHING



Diameter:  
 Outside: 4-7/8"  
 Inside: 1-1/8"  
 Teeth: 11



**RH 826** - 1/2"  
**RH 827** - 5/8"  
 Length: 1-1/4"

NOTE: Please specify 1/2" or 5/8" bolt

- RH 794 or RH 795 F CAST WASHER**

**RH 794** - 1/2" hole  
**RH 795 F** - 5/8" hole  
 Diameter: 1-3/4"



### MAIN DRIVE SPROCKET

- RH 861 MAIN DRIVE SPROCKET**

Diameter:  
 Outside: 5-5/8"  
 Inside: 2-1/8"  
 Holes: 7/16"  
 Hole spacing: 2-1/4"  
 Teeth: 13



### BOOT POINTS

- RH 866 REGULAR POINT**

Length: 4-1/2"  
 Thickness: 1-3/4"  
 Web thickness: 5/8"  
 Holes: 7/16"  
 Hole spacing: 2-1/4"



- RH 868 ROCK POINT**

Length: 4-3/4"  
 Thickness: 1-3/4"  
 Web thickness: 5/8"  
 Holes: 7/16"  
 Hole spacing: 2-1/4"



# R & H Chrome Alloy ROD WEEDER PARTS

## TO FIT: CALKINS

### CENTER DRIVE SPROCKET and COLLAR

**RH 801 CENTER DRIVE SPROCKET**

**RH 805 WEAR COLLAR** for RH 801



Diameter: 4-7/8"  
Width: 2"  
Teeth: 11



Collar diameter:  
Outside: 3-1/8"  
Inside: 1-7/8"

NOTE: Please specify 7/8", 1", or hex rod

### HYDRAULIC DRIVE SPROCKET

**RH 828 A HYDRAULIC DRIVE SPROCKET**  
for 1" shaft

Diameter: 4-7/8"  
Width: 1-5/16"  
Teeth: 11



### IDLER SPROCKET ASSEMBLY

**RH 825 A IDLER SPROCKET** with BUSHING



Diameter:  
Outside: 4-7/8"  
Inside: 1-1/8"  
Teeth: 11



**RH 826** - 1/2"  
**RH 827** - 5/8"  
Length: 1-1/4"

NOTE: Please specify 1/2" or 5/8" bolt

**RH 794 or RH 795 F CAST WASHER**

**RH 794** - 1/2" hole  
**RH 795 F** - 5/8" hole  
Diameter: 1-3/4"



### SPOOLS and WEAR BLOCKS

**RH 810 BARREL SPOOL**

Length: 1-7/8"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

**RH 812 BARREL SPOOL** with SET-SCREW COLLAR

Length: 2-5/8"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

**RH 813 WEAR BLOCK** for RH 810 and RH 812

Holes: 3/8"  
Hole spacing: 1-1/2"



**RH 814 STRAIGHT-SIDED SPOOL**

Length: 1-5/8"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

**RH 815 WEAR BLOCK** for RH 814

Holes: 3/8"  
Hole spacing: 1-1/2"



# R & H Chrome Alloy ROD WEEDER PARTS

TO FIT: CALKINS, cont'd.

## MAIN DRIVE SPROCKET

### RH 802 MAIN DRIVE SPROCKET

Diameter: 9-3/8"  
Teeth: 22  
Holes: 3/8"  
Hole spacing: 2-13/16"



## GOOSE-NECK POINTS

### RH 816 A STANDARD GOOSE-NECK POINT

Length: 15"  
Width: 3-1/2"



Chrome Alloy rod (RH 16) pre-welded onto leading edge of 3/8" T-1 steel.

### RH 816 SE SINGLE-END GOOSE-NECK POINT

Length: 16"  
Width: 3-1/2"



Chrome Alloy rod (RH 16) pre-welded onto leading edge of 3/8" T-1 steel.

## BOOT POINTS

### RH 820 BOOT POINT - REGULAR

Height: 4-1/2"  
Thickness: 1-1/2"  
Web thickness: 5/8"  
Holes: 5/8"  
Hole spacing: 1-7/8"



### RH 821 BOOT POINT - to fit CULTA-WEEDER

Height: 5-1/2"  
Thickness: 1-5/8"  
Web thickness: 1"  
Holes: 5/8"  
Hole spacing: 1-7/8"



### RH 822 BOOT POINT - ROCK

Height: 4-1/2"  
Thickness: 1-1/2"  
Web thickness: 5/8"  
Holes: 5/8"  
Hole spacing: 1-7/8"



### RH 824 BOOT POINT - ROCK

Height: 4-1/2"  
Thickness: 1-3/4"  
Web thickness: 1"  
Holes: 5/8"  
Hole spacing: 1-7/8"



### RH 823 BOOT POINT - UNIVERSAL

Height: 6-1/4"  
Thickness: 1-5/8"  
Web thickness: 5/8"  
Holes: 5/8"  
Hole spacing: 1-7/8"



# R & H Chrome Alloy ROD WEEDER PARTS

## TO FIT: JOHN DEERE

### CENTER DRIVE SPROCKETS

#### RH 831 CENTER DRIVE SPROCKET

Diameter: 4-1/4"  
Width: 2"  
Teeth: 9



NOTE: Please specify 7/8" or 1" rod

#### RH 832 HEX-CENTER DRIVE SPROCKET

Diameter: 4-1/4"  
Width: 2"  
Teeth: 9



NOTE: for 1" hex rod

### 500 SERIES COLLAR and BOOT POINT

#### RH 835 WEAR COLLAR

Collar diameter:  
Outside: 2-7/8"  
Inside: 1-3/4"



#### RH 850 BOOT POINT

Length: 5-1/4"  
Thickness: 2-1/8"  
Web thickness: 1-1/2"  
Holes: 7/16"  
Hole spacing: 2-1/8"



### 800 SERIES COLLAR and BOOT POINT

#### RH 838 WEAR COLLAR

Collar diameter:  
Outside: 2-3/4"  
Inside: 1-3/4"



#### RH 851 BOOT POINT

Length: 9"  
Thickness: 2"  
Web thickness: 1-1/8"  
Holes: 7/16"  
Hole spacing: 3-5/8"



### IDLER SPROCKET ASSEMBLY

#### RH 855 A IDLER SPROCKET with BUSHING

Diameter:  
Outside: 4-1/4"  
Inside: 1-1/8"  
Teeth: 9



**RH 856 - 1/2"**  
Length: 1-1/4"

#### RH 794 CAST WASHER

Diameter: 1-3/4"  
Hole: 1/2"



### SPOOLS and WEAR BLOCK

#### RH 842 SPOOL with SET-SCREW COLLAR

Length: 2-3/4"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

#### RH 844 SPOOL

Length: 2"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

#### RH 845 WEAR BLOCK for RH 842 or RH 844

Holes: 3/8"  
Hole spacing: 1-3/4"



### RATCHET DETENT

#### RH 858 RATCHET DETENT

Length: 4-7/8"  
Slot: 3/8" x 3/16"



### GOOSE-NECK POINTS

#### RH 846 A STANDARD GOOSE-NECK POINT

Length: 16"  
Width: 3-1/2"

Chrome Alloy rod (RH 16)  
pre-welded onto leading  
edge of 3/8" T-1 steel.



# R & H Chrome Alloy ROD WEEDER PARTS

## TO FIT: MORRIS

### CENTER DRIVE SPROCKET and COLLAR

#### RH 871 HEX-CENTER DRIVE SPROCKET for 1" HEX

Diameter: 3-3/4"  
Width: 2-1/8"  
Teeth: 8



#### RH 873 WEAR COLLAR

Collar diameter:  
Outside: 2-7/8"  
Inside: 1-5/8"



### WELD-ON DRIVE SPROCKET

#### RH 879 DRIVE SPROCKET

Diameter:  
Outside: 3-7/8"  
Inside: 2"  
Teeth: 9



### BOOT POINT

#### RH 886 REGULAR POINT

Length: 6-3/4"  
Thickness: 1-3/4"  
Web thickness: 7/8"  
Threaded insert:  
two 1/4" bolts  
1" spacing  
Bolt hole (face): 7/16"



#### RH 887 LEFT and RIGHT REPLACEABLE BOLT-ON SIDE PLATES

Length: 7"  
Holes:  
one 3/8"  
two 1/4"



### SPOOL and WEAR BLOCKS

#### RH 875 SPOOL - for 1" HEX ROD

Length: 2-1/8"  
Diameter: 2-3/8"



#### RH 877 WEAR BLOCK for RH 875

Length: 2-1/2"



#### RH 878 WEAR BLOCK for ROUND ROD

Length: 5-3/4"  
Notch: 3/8"



### GOOSE-NECK POINTS

#### RH 881 A TIP for GOOSE-NECK

Length: 7-1/2"  
Hole: 5/16"



Chrome Alloy strip pre-welded onto leading edge.

#### RH 882 A GOOSE-NECK POINT

Length: 12-1/2"  
Width: 3-1/2"




Chrome Alloy rod (RH 16) pre-welded onto leading edge. of T-1 steel

# R & H Chrome Alloy ROD WEEDER PARTS

## TO FIT: FLEX KING CENTER DRIVE SPROCKET and COLLAR

**RH 831 CENTER DRIVE SPROCKET**  
**RH 835 WEAR COLLAR**



Diameter: 4-1/4"  
Width: 2"  
Teeth: 9  
Collar diameter:  
Outside: 2-7/8"  
Inside: 1-3/4"

NOTE: Please specify 1", 7/8" or 3/4" rod

## SPOOLS and WEAR BLOCKS

**RH 898 SPOOL**

Length: 2-7/8"  
Diameter: 2"



NOTE: Please specify 7/8" or 3/4" rod

**RH 897 WEAR BLOCK**

Length: 3-7/8"  
Width: 2"  
Hole: 3/8"



**RH 842-7/8 SPOOL with SET-SCREW COLLAR**  
**RH 844-7/8 SPOOL**



Length: 2-3/4"  
Diameter: 2-1/4"

Length: 2"  
Diameter: 2-1/4"

**RH 845 WEAR BLOCK for RH 842 or RH 844**

Holes: 3/8"  
Hole spacing: 1-3/4"



## BOOT POINT

**RH 896 BOOT POINT**

Height: 5-1/4"  
Thickness: 2"  
Web thickness: 1-1/2"  
Bolt holes: 7/16"  
Hole spacing: 2-1/8"



## TO FIT: EDWARDS IDLER SPROCKET ASSEMBLY

**RH 825 E IDLER SPROCKET**  
**RH 827 E BUSHING**  
**RH 795 F CAST WASHER**



Diameter: 1-3/4"  
Hole: -5/8"

Outside: 1-1/8"  
Inside: 5/8"  
Length: 3/4"

Diameter: 4-7/8"  
Width 3/4"  
Teeth: 11

## SPOOLS and WEAR BLOCK

**RH 842 SPOOL with SET-SCREW COLLAR**

Length: 2-3/4"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

**RH 844 SPOOL**

Length: 2"  
Diameter: 2-1/4"



NOTE: Please specify 7/8" or 1" rod

**RH 847 WEAR BLOCK for RH 842 or RH 844**

Length: 2-1/2"  
Width: 1-3/4"  
Slot: 1/2" x 3/4"



## TO FIT: ANDERSON and LEON

**RH 891 CENTER DRIVE SPROCKET - 1-1/8" ROUND ROD**  
**RH 892 WEAR COLLAR**



Outside: 2-1/2"  
Inside: 1-5/8"

Diameter: 4"  
Width: 2"  
Teeth: 9